

FS-1118MFP

A4 MONOCHROME MULTIFUNCTIONAL

► print ► copy ► scan ► fax

TIME TO SHARE WITH A SMALL MULTIFUNCTIONAL THAT'S BIG ON PERFORMANCE.

This compact network multifunction device is top of the class in reliability and efficiency. Our unique long-life ECOSYS technology provides cost-efficient productivity in a multitasking environment. The perfect choice when you want print and copy functions as well as the ability to scan in colour and send faxes.

- 18 pages per minute with 1,200 dpi quality
- 96 MB memory for advanced functions (max. 320 MB)
- Standard network interface
- Full colour scanning
- Long-life technology, easy maintenance
- Low total cost of ownership

Product depicted includes optional extras

300-sheet paper capacity as standard. To increase productivity, upgrade to 550 sheets input capacity.



The optional document processor allows you to scan, copy or fax up to 50 pages of originals.



ECOSYS[®]

KYOCERA

FS-1118MFP

A4 MONOCHROME MULTIFUNCTIONAL



ECOSYS technology is based on extremely durable components. The drum, developer and fuser of the FS-1118MFP are designed for 100,000 pages. As toner is the only consumable required, ECOLaser printers operate with the lowest cost per page in their class, and they are particularly environmentally friendly. Thanks to their modular system and flexible paper options all ECOLaser printers can be configured to meet your exact requirements.

System platform:

The FS-1118MFP offers USB, parallel and network connectivity as standard and delivers problem-free system administration. Kyocera's single platform technology means that the same driver can be used for every Kyocera PCL/PostScript print device on the network; from single-user desktop printers to high-end multifunctional systems. Only Kyocera offers this effortless combination of IT sophistication and high-performance paper handling expertise.

PRESCRIBE IIe:

With the Kyocera page design and control language PRESCRIBE IIe, even complex graphics, logos and forms (even multipart forms) can be created independently of the system and saved and updated in the printer. Consequently, integration into print files no longer applies. They are only accessed as required and therefore relieve the load on the network.

KM-NET for Client/KM-NET Viewer:

The settings of all printers on the network can be checked visually and amended from any Windows® PC. KM-NET for Client enables easy setup and monitoring of the printer status via parallel, USB or network connection. KM-NET Viewer is an advanced printer management software tool using the standardized protocol SNMP.

GENERAL

Technology: Kyocera Laser, Mono component
Engine speed: Max. 18 pages A4 per minute
Resolution: 600 x 600 dpi, 256 greyscales (scan/copy), Fast 1,200 dpi quality with KIR2 (print)
Time to first copy: 9.5 seconds or less
Time to first print: 8.0 seconds or less
Warm-up time: 20 seconds or less
Duty cycle: Max. 10,000 pages per month
Power source: AC 220 ~ 240 V, 50/60 Hz
Power consumption: Copying/Printing: 409 W, Stand-by: 76 W, Power-Saving (ECOpower): 40 W
Noise (ISO 7779): Copying/Printing: 65 dB(A), Stand-by: 43 dB(A)
Dimensions (W x D x H): 496 x 421 x 385 mm
Weight: Main unit: Approx. 14.5 kg
Certifications: TÜV/GS, CE
This product is manufactured according to ISO 9001 quality standard and ISO 14001 environmental standard.

PAPER HANDLING

All paper capacities quoted are based on a paper thickness of max. 0.11 mm. Please use paper recommended by Kyocera under normal environmental conditions.

Input capacity: 250-sheet universal paper feeder, 60-105 g/m², A4, B5, A5, A6, Letter, Legal, Folio
50-sheet multi-purpose tray, 60-163 g/m², A4, B5, A5, A6, Letter, Legal, Folio, Custom (105 x 148 to 216 x 356 mm), envelopes
Max. input capacity with options: 550 sheets
Output capacity: 150 sheets face-down, 30 sheets face-up

COPY FUNCTIONS

Max. original size: A4, Folio
Continuous copying: 1-999
Memory capacity: Standard 96 MB, max. 320 MB, 1 additional DIMM slot (64, 128, 256 MB)
Zoom range: 50-200% in 1% steps
Preset magnification ratios: 6R / 4E
Digital features: Scan-once-print-many, electronic sort, auto start, auto cassette change, density adjustment, paper size selection, layout mode (2in1, 4in1), program, interrupt, ECOcopy mode, job reservation, department code (20 codes)
Exposure mode: Auto, manual: 7 steps
Image adjustments: Text + photo, text, photo

PRINT FUNCTIONS

Processor: PowerPC 750Cxr / 300 MHz
Memory: Standard 96 MB (64 MB + 32 MB DIMM), max. 320 MB (1 additional DIMM slot for 64, 128, 256 MB)
Emulations: PCL6/PCL5e incl. PjL, KPDL 3 (PostScript 3 compatible) with automatic emulation sensing (AES), Line Printer, IBM Proprinter X24E, Epson LQ-850, Diablo 630
Controller language: PRESCRIBE IIe
Fonts: 80 outline fonts accessible in all emulations, 1 bitmap font (PCL, KPDL2), 45 types of one-dimensional barcodes, plus two-dimensional barcode (PDF-417)
Features: PDF direct printing, IPP printing, E-mail printing

INTERFACES

Standard interface: High speed bi-directional parallel (IEEE 1284), USB 2.0 (Hi-Speed), Fast Ethernet 10/100Base-TX standard
Multiple interface connection (MIC): Allows simultaneous data transfer via up to three interfaces, with each interface having its own virtual printer.

COLOUR SCAN FUNCTIONS

Functionality: Scan-to-Email, Scan-to-FTP, Scan-to-SMB, TWIN, LDAP
Scan speed: Max. 18 originals per minute (600 dpi / A4, b/w)
Scan resolution: 600, 400, 300, 200 dpi (256 greyscales)
Maximum scan size: A4, Folio
Original recognition: Text, photo, text + photo OCR
Interface: 10/100Base-TX, USB 2.0 (TWIN only)
Network protocol: TCP/IP
File types: TIFF (b/w only), PDF, JPEG (colour only)
Compression format: MMR/JPEG
Applicable PC: IBM PC/AT compatible
Applicable OS: Windows® 98, 98SE, Me, NT4.0, 2000, XP
Bundled software: PaperPort Deluxe 9.2

FAX FUNCTIONS (OPTIONAL)*

Compatibility: ITU-T Super G3
Modem speed: Max. 33.6 kbps
Transmission speed: 3 seconds or less (JBIG)
Scanning speed: 2.5 seconds
Scanning density: Normal: 8 dot/mm x 3.85 line/mm, Fine: 8 dot/mm x 7.7 line/mm, Superfine: 8 dot/mm x 15.4 line/mm, Ultrafine: 16 dot/mm x 15.4 line/mm
Maximum original size: A4, Folio
Compression method: JBIG, MMR, MR, MH
Memory: Standard 6 MB
Fax features: Network faxing, confidential, polling transmission and reception, broadcast, sub-code, document box, remote diagnosis

*Requires optional document processor DP-100

OPTIONS

Fax system (K)

Paper handling

DP-100 Document feeder: 50 sheets, 50-120 g/m², A5R-A4R, Folio

PF-17 Paper feeder: 250 sheets, 60-105 g/m², A4, B5, A5, Letter, Legal, Custom (148 x 210 mm to 216 x 297 mm)

CB-100 Cabinet: Wooden desk with storage capacity, including castors (wheels)

Memory

1 DIMM slot (64, 128, 256 MB)

CONSUMABLES

TK-18 Toner kit: Microfine toner for 7,200 pages with 5% coverage (ISO 10561B)

Capacity of starter toner for 3,600 pages with 5% coverage (ISO 10561B)

WARRANTY

2-year warranty as standard. Kyocera guarantees the drum and developer for 3 years or 100,000 pages (whichever occurs sooner), provided each printer is used and cleaned in accordance with the service instructions.

KYO LIFE KYOlife 3-year on-site warranty for printer and options.



Your Kyocera Business Partner:

Kyocera Mita Europe B.V., Hoeksteen 40, 2132 MS Hoofddorp, The Netherlands, Tel +31 (0) 20 65 40 000, Fax +31 (0) 20 65 31 256, www.kyoceramita-europe.com, info@kyoceramita-europe.com
Kyocera Mita Corporation, 2-28, 1-Chome, Tamatsukuri, Chuo-Ku, Osaka 540-8585, Japan, www.kyoceramita.com

FS-1118MFP-English-8DSE1118. Kyocera does not warrant that any specifications mentioned will be error-free. Specifications are subject to change without notice. Information is correct at time of going to press. All other brand and product names may be registered trademarks or trademarks of their respective holders and are hereby acknowledged.

